



REV.	REVISIONS	REC.	DATE.	REV.	REVISIONS	REC.	DATE.
B	顶部凸点加大至 $\varnothing 2.0$, PIN座底部增加加强肋.		2009. 8. 15	E	防呆凸点高度由1.0改为1.5mm		13. 7. 27
C	PIN 台及弧宽 $\varnothing 0.5$ 角和 $R0.5$; 更改顶部凸台形状.		2009. 9. 22				
D	更改顶部凸台.		2010. 3. 12				

DRAWN DRAFTED BY	HQH	TOLERANCES		ANGLE:	TITLE:		
		$0 < L \leq 4$	± 0.1	PIN PITCH	$\pm 1^\circ$	RM-8	
CHECKED APPROVED BY	HZP	$4 < L \leq 16$	± 0.2		UNIT:	BOBBIN MATERIAL:	UL REC.
		$16 < L \leq 63$	± 0.3	MM	PHENOLIC	UL 94V-0	
壁 厚 ± 0.15				SCALE:	TERMINAL MAT:	PIN TENSION LOAD:	
				1/1	CP WIRE	1.0kg MIN	
MX 东莞市铭兴电子有限公司 DONG GUAN MING XING ELECTRONICS CO., LTD TEL: 0769-86369622 86011822 FAX: 0769-86369611				DATE:	DRAWING NO:	REV.	
				2010. 6. 29	MX-0809	E	