



| REV. | REVISIONS | REC. | DATE. | REV. | REVISIONS | REC. | DATE. |
|------|-----------|------|-------|------|-----------|------|-------|
|      |           |      |       |      |           |      |       |
|      |           |      |       |      |           |      |       |
|      |           |      |       |      |           |      |       |

|   |     |              |           |             |               |                   |          |
|---|-----|--------------|-----------|-------------|---------------|-------------------|----------|
| DRAWN<br>DRAFTED BY   | HQH | TOLERANCES   |           | ANGLE:      | TITLE:        |                   |          |
|   |     | 0<L≤4 ±0.1   | PIN PITCH | ±1°         | EF-12.5       |                   | UL REC.  |
| CHECKED<br>APPROVED BY  | HZP | 4<L≤16 ±0.2  |           | ±0.20       | UNIT:         | BOBBIN MATERIAL:  | UL 94V-0 |
|   |     | 16<L≤63 ±0.3 | MM        |             | PHENOLIC      | PIN TENSION LOAD: |          |
| <b>MX</b> 东莞市铭兴电子有限公司<br>DONG GUAN MING XING ELECTRONCTS CO., LTD<br>TEL:0769-86369622 86011822 FAX:0769-86369611 |     |              |           | SCALE:      | TERMINAL MAT: | 1.0kg             |          |
|   |     |              |           | 1/1         | CP WIRE       |                   |          |
|   |     |              |           | DATE:       | DRAWING NO:   | REV.              |          |
|   |     |              |           | 2010. 6. 15 | MX-1205       | A                 |          |