



REV.	REVISIONS REC.	DATE.	REV.	REVISIONS REC.	DATE.
B	R尺寸由3.55改为3.75	2011.6.21	E	G尺寸由3.9mm改到4.10mm, P尺寸由8.8mm改到9.0mm, 产品PIN台凸点和PIN台挡墙由1.6改到1.8mm	2014.5.16
C	G、P、S尺寸修改	2012.5.31	F	G尺寸由4.10mm改到3.90mm, P尺寸由9.0mm改到8.80mm, 产品PIN台凸点和PIN台挡墙由1.8改到1.6mm, O尺寸由6.2mm改到6.3mm	2014.7.2
D	G尺寸由3.8mm改到3.9mm, P尺寸由8.7mm改到8.8mm, 产品PIN台凸点和PIN台挡墙由1.5改到1.6mm	2013.7.10	G	J尺寸由3.4mm改到3.9mm, K尺寸由20mm改到20.50mm,	2014.8.30
H	5PIN支点头部倒角R0.4MM	2015.9.17			

DRAWN	HQH	TOLERANCES		ANGLE:	TITLE:		
DRAFTED BY	HQH	0<L≤4 ±0.1	PIN PITCH	±1°	EFD16		
CHECKED	HQP	4<L≤16 ±0.2			UNIT:	BOBBIN MATERIAL:	UL REC.
APPROVED BY		16<L≤63 ±0.3					
		壁厚 ±0.15	±0.20		TERMINAL MAT:	PIN TENSION LOAD:	
MX 东莞市铭兴电子有限公司		TEL: 0769-86369622	SCALE:	CP WIRE		2.0kg	
DONG GUAN MING XING ELECTRONCTS CO., LTD		FAX: 0769-86369611	1/1	DATE:	DRAWING NO:	REV.	
MX 靖江市铭翔电子有限公司		TEL: 0523-84523228		2010.08.11	MX-1650	H	
JING JIANG MING XIANG ELECTRONCTS CO., LTD		FAX: 0523-84521028					