



REV.	REVISIONS REC.	DATE.	REV.	REVISIONS REC.	DATE.
B	C尺寸由18.4mm改到19.20mm, C1尺寸由7.30mm改到8.1mm, J尺寸由21.7mm改到22.5mm.	2012. 10. 25	E	产品总长改小0.05mm, 长PIN台挂线凸点改小0.15mm, 长PIN台挡墙加C角	2014. 3. 14
C	产品短PIN台增加两个过线槽, PIN台和挡墙根部C角由0.5mm改到0.6mm.	2013. 11. 26	F	调整PIN台支点加强	2015. 10. 24
D	I尺寸由22.5mm改到22.8mm, 主要为短PIN台加长0.3mm	2014. 01. 17			

DRAWN DRAFTED BY WZW	TOLERANCES		ANGLE:	TITLE: EFD1614		
	0<L≤4 ±0.1	PIN PITCH ±0.20	±1°	BOBBIN MATERIAL: PHENOLIC		UL REC. UL 94V-0
CHECKED APPROVED BY HZP	4<L≤16 ±0.2		UNIT: MM	TERMINAL MAT: CP WIRE		PIN TENSION LOAD: 2.0kg
MX 东莞市铭兴电子有限公司 DONG GUAN MING XING ELECTRONICS CO., LTD TEL:0769-86369622 86011822 FAX:0769-86369611			SCALE: 1/1	DATE: 2013. 9. 30	DRAWING NO: MX-1682C	REV. E