



REV.	REVISIONS REC.	DATE.	REV.	REVISIONS REC.	DATE.
B	顶部挡墙由0.6mm改为0.75mm, 跨距由11.20mm改为11.35 $^{+0.05}$ mm	13. 4. 29	E	长PIN台两边各加大0.2mm, 则总宽由14.9mm改为15.3mm	14. 8. 15
C	顶部挡墙由0.75mm改为0.90mm, PIN台降低, 增加斜过线槽	13. 9. 4	F	1\2PIN间槽加深0.5MM (由3.35改为3.85)	15. 11. 6
D	E尺寸由2.2mm改为2.4mm,	14. 4. 29			

DRAWN DRAFTED BY DMJ	TOLERANCES	0<L≤4 ±0.1	ANGLE: ±1°	TITLE: PQ 2518		
		4<L≤16 ±0.2		PIN PITCH	BOBBIN MATERIAL: PHENOLIC	UL REC. UL 94V-0
CHECKED APPROVED BY HZP	16<L≤63 ±0.3	±0.20	UNIT: MM	TERMINAL MAT: CP WIRE	PIN TENSION LOAD: 1.2kg MIN	
	壁厚 ±0.15		SCALE: 1/1	DATE: 2010. 08. 10	DRAWING NO: MX-2542	REV. F
<b>MX 东莞市铭兴电子有限公司</b> DONG GUAN MING XING ELECTRONCTS CO., LTD TEL:0769-86369622 86011822 FAX:0769-86369611						