



防呆字码A

| REV. | REVISIONS | REC. | DATE. | REV. | REVISIONS | REC. | DATE. |
|------|---------------------------|------|---------|------|-----------|------|-------|
| B | 修改排距 | | 13.6.7 | | | | |
| C | PIN台挡墙加4各槽; PIN台挡板加高0.1MM | | 14.6.6 | | | | |
| D | PIN台挡板加高0.5MM | | 15.11.5 | | | | |

| | | | | | | | |
|---|-----|----------------------------------|---|-------------------------|-------------------------|--------------------------|--------------------------------|
| DRAWN DRAFTED BY | ZKZ | TOLERANCES | | ANGLE: $\pm 1^\circ$ | TITLE: PQ-32 | | |
| | | 0<L≤4 4<L≤16 16<L≤63 壁厚 | ± 0.1 ± 0.2 ± 0.3 ± 0.15 | | PIN PITCH ± 0.20 | BOBBIN MATERIAL: | PHENOLIC |
| CHECKED APPROVED BY | HZP | | | UNIT: MM | | TERMINAL MAT: CP WIRE | PIN TENSION LOAD: 1.2kg MIN |
| MX 东莞市铭兴电子有限公司 DONG GUAN MING XING ELECTRONCTS CO., LTD TEL:0769-86369622 86011822 FAX:0769-86369611 | | | | SCALE: 1/1 | DATE: 2009.10.30 | DRAWING NO: MX-3201 | REV. D |