



注:

- 1、MX-3801: 顶部有防呆点 (同半成品), M脚排距47.0MM, PIN距4.5MM。
- 2、MX-3801-1: 顶部有防呆点 (同半成品), M脚排距51.0MM, PIN距4.5MM。
- 3、MX-3801-2: 顶部有防呆点 (同半成品), L脚排距40.0MM, PIN距4.5MM。
- 4、MX-3801-3: 顶部无防呆点 (不同半成品), L脚排距39.0MM, PIN距4.5MM。
- 5、MX-3801-4: 顶部有防呆点 (同半成品), L脚排距42.8MM, PIN距4.5MM。

REV.	REVISIONS	REC.	DATE.	REV.	REVISIONS	REC.	DATE.
B	D尺寸由11.90MM改为11.75MM		15.5.8				

DRAWN DRAFTED BY	HQH	TOLERANCES		ANGLE:	TITLE:		
CHECKED APPROVED BY	HZP	0<L≤4 ±0.1	PIN PITCH ±0.20	±1°	PQ3813		
		4<L≤16 ±0.2		UNIT:	BOBBIN MATERIAL:	UL REC.	
		16<L≤63 ±0.3		MM	PHENOLIC	UL 94V-0	
				SCALE:	TERMINAL MAT:	PIN TENSION LOAD:	
				1/1	CP WIRE	1.0kg MIN	
MX 东莞市铭兴电子有限公司 DONG GUAN MING XING ELECTRONCTS CO.,LTD TEL:0769-86369622 86011822 FAX:0769-86369611					DATE:	DRAWING NO:	REV.
					2012.05.30	MX-3801-2	B